

TSB

Professional Interpretation
System

ENERSOUND



Lifetime
Warranty




This Professional-grade Simultaneous Interpretation System provides superior sound quality and excellent coverage range, combining multi-channel transmitter and receivers, as well as improved reliability and versatility. It features a unique interpreter monitor feature that allows the interpreter to receive direct audio of the speaker's voice to his or her headphones. It can be expanded by adding an unlimited number of additional receivers.

Features:

- Unique Interpreter Monitor Feature.
- 500ft (150m) coverage range.
- Multichannel transmitter and receivers.
- 72-76 MHz FM frequency band.
- Simple plug-and-play set-up.
- Up to 6 systems can be used in the same area for multiple languages or groups.

Ideal for:



Components



R-120 Receiver

- 20 user-selectable channels.
- Superb sound quality.
- LCD screen.
- Innovative and attractive design.
- Robust engineering for maximum reliability and durability.
- Small & lightweight.
- Multiple carrying options: (Belt clip, Neck strap & Velcro arm-band.)
- Channel lock feature.
- 100% digitally tuned.
- Long battery life (up to 55 working hours.)
- Limited lifetime warranty.



T-500 Transmitter

- 17 selectable channels in 72-76 MHz.
- Superb Audio Quality.
- Expandable transmission range of up to 1000ft with external antenna.
- Easy set up and operation.
- Broadcasts to an unlimited number of receivers.
- Multiple inputs and connector types.
- LCD display with backlight.
- Tabletop or rack-mountable.
- FCC/IC approved.
- Limited lifetime warranty.



EAR-120 Earphones

Dual earphones specially designed to optimize audio quality on R-120 receivers, featuring a 3.5 mm stereo plug.



MIC-300 PRO Headband Microphone

- 360° adjustable and rotating microphone arm with metallic gooseneck for perfect voice pickup.
- Superb mechanical properties.
- High audio quality.
- Wire cleverly set around the neck for the best concealed effect.
- Metal core neck band with a smooth plastic sleeve for maximum comfort.
- Features a 3.5mm TS plug.

Accessories



CAS-10 Carrying Case

- Holds up to 10 Enersound FM receivers.
- Convenient compartment for headphones and other accessories.
- Metal core hinges.
- Nylon latches.
- Integrated handle.
- Strong polypropylene body.
- Convoluted polyurethane foam on lid to gently secure items.
- Custom die cut polyethylene foam divisions.



CAS-25 Carrying and Shipping Case

- Holds up to 25 Enersound FM receivers.
- Convenient compartment for headphones and other accessories including a desktop transmitter and microphone.
- Waterproof, impact resistant, crushproof, dustproof.
- Powerclaw™ latching system.
- Soft grip foldable handle.
- Lightweight NK-7™ resin & 100% stainless steel hardware.
- Automatic pressure release valve.
- Padlockable and stackable.
- Convoluted polyurethane foam on lid to gently secure items.
- Custom die cut polyethylene foam divisions.



CAS-325 Carrying Case

- Holds up to 25 Enersound FM receivers
- Convenient compartment for headphones and other accessories.
- Lightweight.



HEAD-702 Headphones

System Set-up

Audience



**R-120 receivers
with headphones**



**T-500
Transmitter**

Optional PA System



**Interpreter
Microphone
and
headphones**



Technical Specifications

T-500 Transmitter

- Operating Frequency: 72.1-75.9MHz.
- Number of Channels: 17 Selectable.
- Frequency Deviation:
 - Selectable, Wide: +/- 75kHz or
 - Narrow: +/- 25 kHz (Max Deviation.)
- Frequency Accuracy: +/- 0.005%
- Transmitter Stability: +/- 20ppm.
- Output Power:
 - Hi: 80,000uV/m at 3m.
 - Low: 40,000uV/m at 3m.
- Antenna: 50 ohm rubber ducky antenna or optional remote antenna.
- Antenna Connector: Modified TNC.
- Compliance: FCC part15, Industry Canada.
- Frequency Response: 100Hz ~15KHz
- Signal to Noise Ratio: 70db.
- System Distortion:<2%(THD) at 80% dev.
- Audio Input 1: 3-Pin XLR and ¼" (TRS) combination jack for MIC or LINE level Balanced or unbalanced. Nominal input level 0/56dbu (0.77V/1.3mV) (line/mic). Phantom Power:12VDC PIN 2&3 on XLR or Tip and Ring on ¼" TRS Jack.
- Audio Input 2: RCA Jack, unbalanced Line Level -10dBu nominal, 100KΩ.
- External Monitor In: RCA Jack, unbalanced, Line Level -10dBu nominal, 100KΩ.
- REC Output: RCA Jack, unbalance output, Line Level -10dBu nominal, 10 ohms.
- MIC Input: Front panel: 3.5mm 1/8" TRS jack, supplies +DC on tip for electret mics.
- Audio Processing:signal compression 2:1.
- Headphone Out: 3.5mm stereo TRS jack, adjustable output level, Max Power 61mW @8ohm, Impedance: 4~16ohm.
- Power Supply: In:100~240VAC, 50-60Hz., Out:15VDC, 1A. Connector: 5.00mm OD, 2.5mm ID, barrel type.

- Temp. Operation: 23F to + 104F.
- Temp. Storage: -4F) to + 140F.
- Humidity: 0~95% Relative Humidity.
- Dimensions (DxWxH): 5" x 5.5" x 2.36"
- Unit Weight: 1.2 lbs. (0.54 Kg.)
- Shipping Weight: 2.2 lbs. (1.1 Kg.)
- Rack Mounting: 1 1/2 rack space height, 1/2 rack space wide. One or two transmitters can be mounted in 1 1/2 rack space with optional rack mounts RM-501 or RM-502.

R-120 Receivers

- Batteries: (2) alkaline AAA (1.5V x 2) Or (2) NiMH AAA rechargeable.
- Battery life:
 - Up to 55 hours of use w/alkaline batteries.
 - Up to 40 hours w/NiMH rechargeable.
- Number of channels: 20 user-selectable.
- Frequency range: FM 72.0 to 76.0 MHz.
- FM deviation: +/- 75 KHz.
- De-emphasis: 75 uS.
- Sensitivity: 1.12 uV at 12 db SINAD.
- Signal to noise ratio: 55 db at 100 uV.
- Audio frequency response: 80 Hz to 12 Khz.
- Audio power:33 mW +33 mW at 32 ohms.
- Audio connector: 3.5mm stereo phone jack.
- Current consumption: 22 mA nominal.
- Dimensions: 3" Diameter,1.22" High
- Weight without batteries: 2.3 ounces (65g.)