

25-Person Professional Simultaneous Interpretation System for 3 Languages with Full Relay Capabilities | **TSP12-25**

The Enersound TSP12-25 Professional System is designed to work when multiple target languages and full relay capabilities are needed. This 25-person Professional Wireless Simultaneous Translation System provides superior sound quality and excellent coverage range, combining multichannel transmitters and receivers, as well as 12-channel interpreter consoles with full relay capabilities. It can be expanded by adding an unlimited number of additional receivers with headphones. More foreign languages can be added for a maximum of 6 in the same room by purchasing 1 extra transmitter, console and set of headsets per additional target language. This system is ideal for multilingual conferences, meetings, court proceedings, and more.

Note: This system requires a human language interpreter, it does not translate automatically.



T-500 Multichannel Base Transmitter



CU-12 Control Unit



IC-12 Interpreter Console



Interpreter Headset



R-120 Multichannel FM Receiver

System Includes:

- (25) R-120 Multichannel FM Receivers
- (25) EAR-120 Dual Headphones for audience
- (3) T-500 Multichannel Base Transmitter
- (3) ANT-500 Helical Antenna
- (3) PS-500 Power Supply
- (4) Plantronics Headset
- (2) IC-12 Interpreter Console
- (1) CU-12 Control Unit
- (2) CBL25-6 25-pin 6m cable for IC-12



EAR-120 Dual Headphones



CBL25-6 25-pin 6m cable



Optional
CAS-25 Carrying Case

Additional info...

This system is equipped with IC-12 Interpreter Consoles, 12-channel dual interpreter console with full relay capabilities. Each console allows two interpreters to work together. Interpreters can choose either floor channel to listen to the speaker and perform direct interpretation or choose the relay mode (when the interpreter does not understand the floor language) and listen to the interpretation from a different booth in a language that this interpreter can understand. Unlike other interpreter consoles in the market, this relay mode is a true channel selectable relay function with audio level buster that allows the interpreter to select any of the 11 languages as their source language for the relay interpretation.

Audience



Delegate Wireless Receivers



UP TO 12 WIRELESS TRANSMITTERS

TRANSMITTER 1
ENGLISH

TRANSMITTER 2
SPANISH

TRANSMITTER 3
FRENCH



EXTERNAL PA SYSTEM



FLOOR INPUT

CU-12 CONTROL UNIT

UP TO 11 IC-12 INTERPRETER CONSOLES



SPANISH
BOOTH



FRENCH
BOOTH

*THIS IS A SAMPLE SCENARIO. LANGUAGES AND COMBINATIONS MAY CHANGE